




SAFETY DATA SHEET

WHMIS 2015 • OSHA HCS (29 CFR 1910.1200) • NOM-018-STPS-2015

1. SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier**
Product Name **Silmer G-223 A**
Product code 6972.72
Chemical Name Mixture
CAS No. 25036-25-3 / 69669-36-9 / 67762-95-2 / 1330-20-7 / 100-41-4
- 1.2 Recommended use of the chemical and restrictions on use**
Identified use(s) intermediate use
Uses advised against None known
- 1.3 Details of the supplier of the Safety Data Sheet**
Company Identification Siltech Corp
225 Wicksteed Ave
Toronto, ON Canada M4H 1G5
Telephone +1-416-424-4567
Fax +1-416-424-3158
E-Mail (competent person) raj@siltech.com
- Additional Location Siltech Corp
3265 Wolfedale Road,
Mississauga ON Canada L5C 1V8
Telephone +1-905-270-5534
Fax +1-905-270-5816
- 1.4 Emergency telephone number**
Emergency Phone No. **CANUTECH - TELEPHONE: EMERGENCY USE ONLY
+1-613-996-6666**

2. SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture**
Flam. Liq. 3
Acute Tox. 4 – Dermal
Acute Tox. 4 - Inhalation
Skin Irrit. 2
Eye Irrit. 2
Skin Sens. 1
STOT RE 2 - Hearing deterioration
- 2.2 Label elements**
Product Name **Silmer G-223 A**
Symbol 
- Signal word(s) **WARNING**
Hazard statement(s) H226: Flammable liquid and vapour.
H312: Harmful in contact with skin.
H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H319: Causes serious eye irritation.
H332: Harmful if inhaled.
H373: May cause damage to organs through prolonged or repeated exposure.

Precautionary statement(s)

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P240: Ground/bond container and receiving equipment.
 P241: Use explosion-proof electrical/ventilating/lighting/equipment.
 P242: Use only non-sparking tools.
 P243: Take precautionary measures against static discharge.
 P260: Do not breathe dust/fume/gas/mist/vapours/spray.
 P264: Wash hands and exposed skin thoroughly after handling.
 P271: Use only outdoors or in a well-ventilated area.
 P272: Contaminated work clothing should not be allowed out of the workplace.
 P280: Wear protective gloves/protective clothing/eye protection/face protection.
 P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
 P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P304+P312: IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.
 P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337+P313: If eye irritation persists: Get medical advice/attention.
 P363: Wash contaminated clothing before reuse.
 P403+P235: Store in a well-ventilated place. Keep cool.
 P501: Dispose of contents/container to: Observe Local Regulations.
 None known

2.3 Other hazards

3. SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Mixtures

Hazardous ingredient(s)	Synonym(s)	%W/W	CAS No.	EC No.	Hazard pictogram(s) and Hazard statement(s)
Phenol; 2,2'-[[1-methylethylidene]bis(4,1-phenyleneoxymethylene)] bis[oxirane]	Bisphenol (Epoxy Resin)	30 - 35	25036-25-3	682-390-8	GHS07 H315, H317, H319
Xylene	Dimethylbenzene	6 - 10	1330-20-7	215-535-7	GHS02, GHS07 H226, H312, H315, H332
Ethylbenzene	EB	0.4 - 4	100-41-4	202-849-4	GHS02, GHS08, GHS07 H225, H332, H304, H373

4. SECTION 4: FIRST AID MEASURES



4.1 Description of first aid measures

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing. If symptoms persist, obtain medical attention.

Skin Contact	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If irritation develops and persists, get medical attention.
Eye Contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
Ingestion	IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Get medical attention immediately.
4.2 Most important symptoms and effects, both acute and delayed	May cause an allergic skin reaction. Causes skin irritation. Causes severe eye irritation.
4.3 Indication of any immediate medical attention and special treatment needed	No information available.

5. SECTION 5: FIRE-FIGHTING MEASURES

5.1 Extinguishing Media	
Suitable Extinguishing Media	In case of fire, use water spray, foam, dry powder or CO2 for extinction. Keep containers cool by spraying with water if exposed to fire.
Unsuitable Extinguishing Media	Do not use water jet.
5.2 Special hazards arising from the substance or mixture	No information available.
5.3 Advice for fire-fighters	A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions.

6. SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures	Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.
6.2 Environmental precautions	Avoid release to the environment.
6.3 Methods and material for containment and cleaning up	Caution - spillages may be slippery. Cover spills with inert absorbent material. Transfer to a container for disposal.
6.4 Reference to other sections	See Section: 7 & 8.

7. SECTION 7: HANDLING AND STORAGE




7.1 Precautions for safe handling	Avoid contact with skin and eyes. Avoid ingestion. Use only with sufficient ventilation. Wash thoroughly after handling. General hygiene measures for the handling of chemicals are applicable. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
7.2 Conditions for safe storage, including any incompatibilities	Store in a tightly closed container. Keep away from heat and light.
Storage Temperature	Ambient
Storage Life	Stable under normal conditions.
Incompatible materials	Oxidizing agents
7.3 Specific end use(s)	Industrial use

8. SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

- 8.1 Control parameters**
8.1.1 Occupational Exposure Limits

SUBSTANCE	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m ³)	STEL (ppm)	STEL (mg/m ³)	Note
Xylene	1330-20-7	100	435	150		
Ethylbenzene	100-41-4	100	435			

- 8.1.2 Biological limit value** Not established

8.1.3 PNECs and DNELs	Not established
8.2 Exposure controls	
8.2.1 Appropriate engineering controls	Provide adequate ventilation when using the material and follow the principles of good occupational hygiene to control personal exposures.
8.2.2 Personal protection equipment	
Eye/face protection	Eye protection with side protection (EN 166)
	
Skin protection (Hand protection/ Other)	Wear impervious gloves (EN374). Nitrile rubber, Polyethylene, PVC Wear suitable protective clothing.
	
Respiratory protection	Wear suitable respiratory protective equipment if processing involves working in areas where dusts or vapours are likely to be evolved.
	
Thermal hazards	None.
8.2.3 Environmental Exposure Controls	Avoid release to the environment.

9. SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties	
Appearance	Colourless to yellowish liquid.
Odour	Characteristic odour.
Odour Threshold	Not available.
pH	Not available.
Melting Point/Freezing Point	Not available.
Initial boiling point and boiling range	Not available.
Flash point (PMCC)	34°C
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density / Specific Gravity (20°C)	Not available.
Solubility(ies)	Not available.
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature	Not available.
Decomposition Temperature	Not available.
Viscosity (25°C)	Not available.
Explosive properties	Not applicable.
Oxidising properties	Not applicable.

10. SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity	Stable under normal conditions.
10.2 Chemical stability	Stable under normal conditions.
10.3 Possibility of hazardous reactions	Will not occur
10.4 Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
10.5 Incompatible materials	Oxidizing agents, Acids, Alkaline
10.6 Hazardous Decomposition Product(s)	Carbon oxides may be formed.

11. SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

Ingestion	Harmful if swallowed.
Inhalation	Harmful by inhalation.
Skin Contact	Causes skin irritation.
Eye Contact	Causes eye irritation.

Effects and Symptoms

skin corrosion/irritation	Causes skin irritation.
Serious eye damage/irritation	Causes serious eye damage.
Respiratory or skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
STOT - single exposure	Not classified
STOT - repeated exposure	Repeated and/or prolonged contact may cause: Hearing deterioration
Aspiration hazard	Not classified
Delayed and chronic effects	Not available
Calculated acute toxicity estimate (ATE)	Not available

12. SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity	Not available.
12.2 Persistence and degradability	Not available.
12.3 Bioaccumulative potential	Not available.
12.4 Mobility in soil	Not available.
12.5 Results of PBT and VPVB assessment	Not available.
12.6 Other adverse effects	None known

13. SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods	Do not empty into drains; dispose of this material and its container in a safe way.
13.2 Additional Information	Dispose of contents in accordance with local, state or national legislation.

14. SECTION 14: TRANSPORT INFORMATION

14.1 UN number	1993
14.2 UN proper shipping name	FLAMMABLE LIQUIDS N.O.S. (Xylene Solution)
14.3 Class	3 Packing group III

15. SECTION 15: REGULATORY INFORMATION

15.1 EU regulations

REACH Registration No.	Polymer exempt / Not available
Candidate List of Substances of Very High Concern for Authorisation	Possible trace amounts of: (<0.05%): Octamethylcyclotetrasiloxane (CAS# 556-67-2) Decamethylcyclopentasiloxane (CAS# 541-02-6) Dodecamethylcyclohexasiloxane (CAS# 540-97-6)

15.2 International Inventories

Country	Listed	Not listed	Polymer exempt	Other
United States (TSCA)	✓			
Canada (DSL/NDSL)	DSL✓			
European Union (EINECS/ELINCS)	✓		✓	
Australia (AICS)	✓			
China (IECSC)	✓			
Japan (ENCS)	✓			
South Korea (KECI)	✓			
Taiwan (TCSI)	✓			
New Zealand (NZIoC)		X		
Philippines (PICCS)		X		

15.3 National regulations

United States (TSCA)

TSCA Inventory Status : All chemicals in this product comply with TSCA rules and regulations including TSCA Section 5 (Inventory Rules).

HMIS (Hazardous Material Information System)
NFPA Rating

H = 2 / F = 3 / R = 0
H = 2 / F = 3 / R = 0

15.4 US State Regulations

15.4.1 SUBSTANCES KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM

Specific Listing(s) not required
Possible trace amounts of:

Ethylene Oxide (CAS# 75-21-8) < 1 ppm

15.4.2 SUBSTANCES KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER

Ethylbenzene (CAS# 100-41-4) 0.4 – 4%
Specific Listing(s) not required
Possible trace amounts of:
Ethylene Oxide (CAS# 75-21-8) < 1 ppm
1,4-Dioxane (CAS# 123-91-1) < 1 ppm

15.4.3 State Right to Know Lists

Xylene (CAS# 1330-20-7) 6 – 10%
Ethylbenzene (CAS# 100-41-4) 0.4 – 4%
Specific Listing(s) not required
Possible trace amounts of:
Ethylene Oxide (CAS# 75-21-8) < 1 ppm
1,4-Dioxane (CAS# 123-91-1) < 1 ppm

16. SECTION 16: OTHER INFORMATION

Revision: **November 29, 2018**

LEGEND

LTEL Long Term Exposure Limit
STEL Short Term Exposure Limit
STOT Specific Target Organ Toxicity
DNEL Derived No Effect Level
PNEC Predicted No Effect Concentration
PBT Persistent, Bioaccumulative and Toxic
vPvB very Persistent and very Bioaccumulative

References:

Hazard statement(s) and Precautionary statement(s)

H226: Flammable liquid and vapour.
H312: Harmful in contact with skin.
H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H319: Causes serious eye irritation.
H332: Harmful if inhaled.
H373: May cause damage to organs through prolonged or repeated exposure:
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240: Ground/bond container and receiving equipment.
P241: Use explosion-proof electrical/ventilating/lighting/equipment.
P242: Use only non-sparking tools.
P243: Take precautionary measures against static discharge.
P260: Do not breathe dust/fume/gas/mist/vapours/spray.
P264: Wash hands and exposed skin thoroughly after handling.
P271: Use only outdoors or in a well-ventilated area.
P272: Contaminated work clothing should not be allowed out of the workplace.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P304+P312: IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313: If eye irritation persists: Get medical advice/attention.
P363: Wash contaminated clothing before reuse.
P403+P235: Store in a well-ventilated place. Keep cool.
P501: Dispose of contents/container to: Observe Local Regulations.

Hazard pictogram(s) and Hazard Symbol



Additional Information

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Siltech Corp. gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Siltech Corp. accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.